

SCREEN PRINTING INK

80UV RANGE

fast and highly reactive

SunChemical®

Coates Screen Inks

The product range for printing on plastic hollow bodies



Technical Data

Ink Type	Screen printing ink
Base:	UV-radiation curing UV-LED curing
Gloss level:	High
Reactivity	High

Please see information on reverse side

Coates Screen Inks GmbH

Nuremberg Screen and Pad Printing Inks
from Wiederholdplatz

Wiederholdplatz 1 · D-90451 Nürnberg
T +49 911 64 22-0 · F +49 911 64 22-200
info.coates@sunchemical.com
www.coates.de

SCREEN PRINTING INK

80UV GRUPPE

fast and highly reactive

Ink ranges of the 80UV product range are the first choice for printing on various types of polyolefine containers (PP, LHD-PE, LD-PE).

All products are supplied in a ready-to-print adjustment and exhibit excellent printability properties. As the inks of the 80UV product range are highly reactive they are best suited for high-speed multi-colour lines.

80UV



Our very successful ink **80UV** is the base of the 80UV range.

80UV: medium viscosity, slightly thixotropic adjustment, highly reactive.

Especially suited for high-speed printing (approx. 100 pcs/min) of „rigid“ technical containers such as PP and HD-PE cartridges on modern fast running multicolour equipment.

Pantone guide formulations are available as data base „UV-container printing mixing formulations C-MIX 2000“.

Option:

Hardener Additive UV/H, addition if required on difficult substrates, such as plastics with a high content of recycled material.

81UV



Compared to 80 UV, **81UV** inks have a modified rheology (higher thixotropy). Alternative to 80UV, for slightly slower printing equipment .

Preferred for printing of buckets and (larger) PP/PE bottles.

Pantone guide formulations are available as data base „UV-container printing mixing formulations C-MIX 2000“.

Option:

Adhesion promoter 551903, addition if required on difficult substrates, such as plastics with a high content of recycled material.

832UV-SF



832UV-SF is free of silicone. Mainly used for the decoration of plastic tubes (LD-PE). 832UV-SF is ideal for combination with flexographic applications, overprinting of 2-component solvent based and UV-curing varnishes as well as (foil) stamping applications with subsequent overprinting.

Highly reactive 832UV-SF can also be cured with UV-LED.

Pantone guide formulations are available as data base „Formula Management C-MIX 2000“.

01/2021

Coates Screen Inks GmbH

Nuremberg Screen and Pad Printing Inks
from Wiederholdplatz

Wiederholdplatz 1 · D-90451 Nürnberg
T +49 911 64 22-0 · F +49 911 64 22-200
info.coates@sunchemical.com
www.coates.de